

Luméa Shell Mosaic Tile Specification

A decorative tile suitable for walls including wet areas

Sizes	25x25mm pieces	10 sheets per m ²	4.5kg
	15x15mm pieces	10 sheets per m ²	3.5kg
Thickness	2.3mm +/-0.2mm including web backing		
Construction	Solid shell pieces glued on 300 x 300 mm web backing.		
Finish	Buff Polished.		
Colours	Made from natural shell types: NZ abalone (Paua), Black Mother of pearl, Freshwater Mother of Pearl.		
Cutting	Cut with a diamond blade tile wet saw or dry masonry blade.		
Installation	<p>Install with 2 pack epoxy adhesive and grouts¹.</p> <p>Because the shell is thinner than normal mosaic's care is needed to get the right volume of adhesive applied using a 1.5 – 2.0 mm notched trowel. Too much adhesive will show through on the finished surface.</p>		
Limitations	<ul style="list-style-type: none"> - Not suitable for places where intense heat may occur, such as fire surrounds, above oven hobs or on benches. - Use only non-abrasive cleaners. - As a natural product, shade, pattern and minor size variation are inherent characteristics. - Not suitable for salt or chlorine swimming pools. - Not suitable for permanent wet areas. - Not recommended below the shower line in of shower. 		

These recommendations are a general guide only. For more specific details please contact us.

¹ e.g Litokol's 'Litoelastic' and 'Starlike' products or Mapei's 'Kerapoxy' and 'Ultracolor Plus'